

DR-T73系列

—组转换型—

3A/1A/1.5A/5A

RoHS
Compliant

特性:

订购信息

触点负载

| DR-T73系列 | 3A | 1A | 1.5A | 5A |
|----------|----------------|----------------|----------------|----------------|
| 尺寸 | 15.5 | 15.5 | 15.5 | 15.5 |
| 触点容量 | 3A/250V | 1A/250V | 1.5A/250V | 5A/250V |
| 触点材料 | Ag | Ag | Ag | Ag |
| 触点电阻 | ≤10mΩ | ≤10mΩ | ≤10mΩ | ≤10mΩ |
| 线圈电压 | AC/DC 12V~250V | AC/DC 12V~250V | AC/DC 12V~250V | AC/DC 12V~250V |
| 线圈功率 | ≤1.2W | ≤1.2W | ≤1.2W | ≤1.2W |
| 寿命 | ≥100,000次 | ≥100,000次 | ≥100,000次 | ≥100,000次 |
| 动作时间 | ≤10ms | ≤10ms | ≤10ms | ≤10ms |
| 恢复时间 | ≤10ms | ≤10ms | ≤10ms | ≤10ms |
| 绝缘电阻 | ≥100MΩ | ≥100MΩ | ≥100MΩ | ≥100MΩ |
| 耐压 | ≥250VAC | ≥250VAC | ≥250VAC | ≥250VAC |
| 存储温度 | 0~70℃ | 0~70℃ | 0~70℃ | 0~70℃ |

| DR-T73系列 | 3A | 1A | 1.5A | 5A |
|----------|----------------|----------------|----------------|----------------|
| 触点容量 | 3A/250V | 1A/250V | 1.5A/250V | 5A/250V |
| 触点材料 | Ag | Ag | Ag | Ag |
| 触点电阻 | ≤10mΩ | ≤10mΩ | ≤10mΩ | ≤10mΩ |
| 线圈电压 | AC/DC 12V~250V | AC/DC 12V~250V | AC/DC 12V~250V | AC/DC 12V~250V |
| 线圈功率 | ≤1.2W | ≤1.2W | ≤1.2W | ≤1.2W |
| 寿命 | ≥100,000次 | ≥100,000次 | ≥100,000次 | ≥100,000次 |
| 动作时间 | ≤10ms | ≤10ms | ≤10ms | ≤10ms |
| 恢复时间 | ≤10ms | ≤10ms | ≤10ms | ≤10ms |
| 绝缘电阻 | ≥100MΩ | ≥100MΩ | ≥100MΩ | ≥100MΩ |
| 耐压 | ≥250VAC | ≥250VAC | ≥250VAC | ≥250VAC |
| 存储温度 | 0~70℃ | 0~70℃ | 0~70℃ | 0~70℃ |

DR-T73系列

一组转换型

7A/10A/15A

安规认证 (相关认证以第三方认证证书为准)

 CCC 14002118659



R502322130005



E105758

10A 250VAC/28VDC

10A 250VAC

15A 125VAC NO

www.darunrelay.com



www.darunrelay.com

14002118659

